

HONDA

UMR435T - GENERAL FEATURES

- Shoulder belt - High strength cloth material and pad fix with belt by sewing
- Engine mount spring - Decreased vibration and increased oil and weather resistance ability
- Robust, lightweight and easy-to-use
- World's first 360° inclinable 4-stroke engine



UMK435T	
Overall Dimensions	
Length	2710mm
Width	565mm
Height	375mm
Weight Dry	10.20kg
Weight Wet	11.26kg
Engine Specifications	
Engine Type	GX35
Displacement	35.8cm ³
Net Power	1.0kW (1.4hp) / 7000rpm
Fuel Tank Capacity	0.63L
Engine Oil Capacity	0.10L
Engine Weight Dry	3.46kg
Engine Weight Wet	4.01kg
Start System	Recoil Starter
Clutch System	Automatic Centrifugal
Shaft Type	Flexible
Noise	112 dB(A)
Frame	
Handle Type	Loop Handle
Throttle System	Trigger Type
Frame Weight	4.04kg
Pipe Diameter	28mm
Drive Shaft	8mm
Blade Type/Size	2-Teeth Blade/12"
Belt	Backpack
Harness	Double shoulder comfort

Optional accessories available

Trimmer Head

Perform Line

Star Blade

8-Teeth Blade

3-Teeth Blade



DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.

