

EG1000 & EP1000 - GENERAL FEATURES

- Environmentally Friendly emits less smoke and pollutants
- Pocket Friendly consumes less fuel and engine oil
- User Friendly petrol operated and easy to use
- Smart Compact Design ergonomically designed handle/frame for better comfort



	EG1000	EP1000
AC Frequency	50Hz	
AC Output VOLTAGE	230V	
Rated AC output	0.75kVA	
Maximum AC output	0.85kVA	
Model	GX80	
Engine Type	Air cooled 4 stroke OHV single cylinder	
Displacement	79.7cc	
Ignition system	Transistorized magneto	
Starting system	Recoil	
Continuous operational time	6.7h	
Fuel tank capacity	3.6 Ltrs	
Dimension (L*W*H)	376 x 302 x 430mm	404 x 352 x 431 mm
Dry weight	22.6 kg	27.4 kg
Noise level	90 dB	86 dB



DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its offic ers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.