

HONDA

EP2500CX & E2500CX - GENERAL FEATURES

- Automatic Voltage Regulator (AVR) System
- 4-stroke OHV Engine
- Easy and reliable starting system
- Large size air cleaner
- AC/DC circuit breaker



	EP2500CX	ER2500CX
<u>Engine</u>		
Model	GX160	GP160
Type	Air-cooled 4-stroke OHV single-cylinder	
Displacement (cc)	163	
Maximum Output (PS) at 3600 RPM	5.5	
Ignition System	Transistorized magneto	
Oil Alert System	YES	
Starting System	Recoil	
<u>Generator</u>		
Voltage Regulation System	AVR	
Phase	Single	
AC Output (kVA) at Maximum	2.2	
Rated Voltage (V)	230 (50Hz)	
DC Output (V-A)	12V - 8.3A	
Rated Power Factor (cos)	1	
<u>Others</u>		
Fuel Tank Capacity (L)	15	
Dimensions [LxWxH] (mm)	590 x 430 x 435	590 x 430 x 460
Weight (kg)	45	40
Sound Level (dB) [db(A)/7m]	65	65
Continuous Operating Hours (hr)	13	11.6



DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.