

# HONDA

## EU10i & EU22i - GENERAL FEATURES

- Super quiet operation - Revolutionary technology and sound proofed casing
- Pure power - Unique inverter technology produces clean and smooth power
- Superb efficiency - Unique ecothrottle runs only as fast as the load demands
- Lightweight and compact - Easy to carry, transport and store
- Spill-free refuelling - Extra wide filler cap for easy filling
- Sturdy platform - Rubberised feet minimise vibration and movement



|                             | EU10i                                   | EU22i              |
|-----------------------------|---|--------------------|
| AC Frequency                | 50Hz                                    |                    |
| AC Output VOLTAGE           | 230V                                    |                    |
| Rated AC output             | 0.9kVA                                  | 1.8kVA             |
| Maximum AC output           | 1kVA                                    | 2.2kVA             |
| DC output                   | 12V-8A                                  |                    |
| Max Power Output            | 1.32kW at 6000 rpm                      | 2.7kW at 3600 rpm  |
| Model                       | GXH50                                   | GXR120             |
| Engine Type                 | Air cooled 4 stroke OHV single cylinder |                    |
| Displacement                | 50cc                                    | 121cc              |
| Ignition system             | Fully Transistorized                    |                    |
| Starting system             | Recoil                                  |                    |
| Continuous operational time | 3h                                      | 3.3h               |
| Fuel tank capacity          | 2.3 Ltrs                                | 3.6 Ltrs           |
| Dimension (L*W*H)           | 450 x 240 x 380mm                       | 511 x 290 x 425 mm |
| Dry weight                  | 13 kg                                   | 21 kg              |
| Noise level                 | 54 dB(A)                                | 91 dB(A)           |



## DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.