

HONDA

EU30is & EU70is - GENERAL FEATURES

EU30is	EU70is
<ul style="list-style-type: none"> - Ultra compact and lightweight for easy transport - Highest quality electricity and powerful parallel operation - Eco-throttle for superior fuel economy - Two-tiered noise dampening for easy use anywhere 	<ul style="list-style-type: none"> - Fuel injection (FI) system increases fuel efficiency - FI system eliminates need of carburetor draining before storage - FI system enables hassle-free push-button engine start



	EU30is	EU70is
	Generator	
AC Frequency	50Hz	
AC Output Voltage	230V	
Rated AC Output	2.8kVA	5.5kVA
Maximum AC Output	3.0kVA	7.0kVA
DC Output	12V-12A	N/A
	Engine	
Model	GX200	GX390
Type	Forced air-cooled 4-stroke OHV single-cylinder	
Displacement	196cm ³	389cm ³
Ignition System	Transistorized magneto	
Starting System	Recoil	
Maximum Power Output	5.2PS(3.82kW)/3600rpm	N/A
Fuel Tank Capacity	13 liters	19.2 liters
Continuous Operating Hours @ Rated Output	7.1hr	6.5hr
Operating Noise Level (at 7m) (1/4 Load - Rated Load)	58dB(A)	85.2dB(A)
	Dimensions	
Dimensions (LxWxH)	655x445x555mm	1016x680x722mm
Dry Weight	59kg	123.2kg



DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.