

**POWERED by**  
**HONDA™**



**EM3600EX** POWERED by HONDA™

**EM5000** POWERED by HONDA™

**EM8000ETS** POWERED by HONDA™

**LIGHT UP  
THIS CHRISTMAS**

**HONDA  
GENERATORS**



**0728 607 525**

Model	EM3600EX	EM5000	EM8000ETS
Rated frequency	50Hz		
Rated voltage	220V		220V/415V
Rated current	12.1A	17.4A	25A/10.4A
Max output power	3000W (3kVA)	4500W (4.5kVA)	6500W (6.5kVA)
Power factor	1		
Engine	HONDA GP200	HONDA GX270	HONDA GX390
	4-stroke OHV single cylinder gasoline		
Displacement	196cc (6.5HP)	270cc (9HP)	389cc (13HP)
Ignition system	Transistorized magneto		
Starting system	Key Start/Recoil	Recoil	Key Start/Recoil
Fuel tank capacity	15L	25L	25L
Continuous operating time	8h	9.5h	8.1h
Noise level	95dBA	96dBA	97dBA
Dry weight	45kg	78kg	94kg
Dimensions [LxWxH]	620 x 480 x 525 mm	710 x 545 x 600 mm	710 x 545 x 600 mm
Wheel kit	Yes	No	Yes

**DISCLAIMER**

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.