MECHANICAL POKER VIBRATORS







HONDA VIBRATING POKERS



ENGINE SPECIFICATIONS				
Engine	GP160	GX160		
Туре	Air-cooled 4-stroke petrol OHV			
Displacement	163 cc			
Compression Ratio	8.5:1			
Max HP/RPM	5.5 HP/3600 RPM			
Fuel Tank Capacity	3.1 L			
Fuel Consumption	1.4 L/h @ 3600 RPM			
Oil Capacity	0.58 L			
Starting System	Recoil starter			
Weight with Frame	20 kg			

POKER SHAFT SPECIFICATIONS				
Model	ZK45 SWE	ENAR 38	ENAR 48	ENAR 58
Shaft Diameter	45 mm	35 mm	45 mm	55 mm
Total Weight	16.5 kg	18.3 kg	20.1 kg	22.2 kg
Total Length	6.590 m	6.375 m	6.445 m	6.450 m
Frequency	12,000 RPM			
Performance	25 m ³ /h	15 m ³ /h	25 m ³ /h	35 m ³ /h

DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.