

pacwell®



Diesel Welding Generator

Reliable, fuel efficient & sophisticated

Characteristics

- Key Start
- With Battery
- With Trolley
- Oil Alert System
- Air Cooled Diesel Engine

Electrode Types

- Ructile
- Steel
- Basic
- Cast Iron
- Stainless Steel

Power Tools Generator

- Drills
- Grinders
- Sanders
- Motors
- Lights



Model		5GF MEW-A F3	5GF MEW-B F3
Welder	Rated Output (kW)	3.64 (4.4 kVA)	4.5 (5.5 kVA)
	Current (A)	160	190
	Voltage (V)	26	26
	Electrode (mm)	2.2-3.2	2.2-4.0
Generator	Rated Output (kW)	2	5
	Frequency (Hz)	50	
	Voltage (V)	220	
Engine	Model	LT 186FA	
	Type	4-stroke vertical air-cooled single cylinder diesel	
Dimensions (LxWxH)(mm)		760 x 500 x 650	
Weight(kg)		108	

Spare Parts

Service Station



Protech Industrial Equipment Ltd.
 24 Kijabe Street | P.O.Box 10076-00100, Nairobi - KENYA
 Wireless 020-2431558 /9 | Mobile 0728 607525 |
 Fax 020-2601187.
 sales@hondapower.co.ke | honda@protech.co.ke

Protech

Quality equipment for premium development project

.....

DISCLAIMER

Whilst Protech Industrial Equipment Ltd and its affiliates takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Protech Industrial Equipment Ltd, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information.

